

## RESEARCH OUTPUTS / RÉSULTATS DE RECHERCHE

### Bright Lights

Sarrazin, Michael

*Published in:*  
American Scientist

*Publication date:*  
2006

*Document Version*  
Publisher's PDF, also known as Version of record

[Link to publication](#)

*Citation for pulished version (HARVARD):*  
Sarrazin, M 2006, 'Bright Lights', *American Scientist*, vol. 94, no. 3, pp. 197-198.

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal ?

### Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



see full issue: May-June 2006

## LETTERS TO THE EDITOR

To the Editors:

In the article "A Bright Future for Subwavelength Light Sources" (January-February), Tineke Thio considered a model involving nonresonant evanescent waves diffraction and interferences to explain the typical transmission spectra through hole arrays, which is observed either with metallic or dielectric films.

However, our own work makes clear that the existence of eigenmodes (bound modes) are required to observe the general features of the hole arrays' transmission, although a strong hypothesis on the origin of the eigenmodes was not required.

The eigenmodes related to the film, whatever the material, are resonantly excited by the incident light and converted into transmitted waves (thanks to the film corrugation). These waves interfere with nonresonantly transmitted waves (due to "Bethe" transmission, for instance). As a consequence, the transmission spectra are well depicted as a series of asymmetrical Fano profiles.

According to the contributions of resonant and nonresonant processes, eigenmode resonance wavelengths can be associated either with transmission peaks or dips. This is likely to be the reason for the transmission dependence against the grooves locations (maintaining the same spacing between them) from the central aperture in the circular arrays, as the nonresonant contribution changes.

According to the material properties, one observes various eigenmodes: surface plasmons (metallic films), guided slab modes or Brewster-Zennek surface modes (dielectric films), surface phonon-polaritons (ionic materials in the reststrahlen band), "Pendry" surface modes (perfectly conducting materials).

Other authors have also confirmed experimentally or theoretically many of these results.

Michaël Sarrazin  
University of Namur, Belgium

Dr. Thio responds:

Many researchers share Dr. Sarrazin's view that a resonance must be implicated in the transmission properties of subwavelength hole arrays. This is entirely reasonable if a hole in an array indeed transmits 1,000 times more light than a solitary hole. However, evidence is accumulating that the enhancement is really at most a factor of 10, and a resonance is not necessary to account for such a modest enhancement. The transmission spectra of hole arrays exhibit a stunning similarity across a large range of geometrical and materials parameters. So instead of indulging in a proliferation of possible resonance modes, let us use Ockham's razor, or the principle of adopting the simplest theory that explains all the observations. The model of diffraction and interference of evanescent waves does the job.